

## Party

|                            |                                |                         |
|----------------------------|--------------------------------|-------------------------|
| <b>Tuft gauge</b>          | 5/32 cut pile                  | ISO 2424                |
| <b>Pilecomposition</b>     | 100% PP                        | ISO 2424                |
| <b>Primary Backing</b>     | Woven                          | ISO 2424                |
| <b>Secondary backing</b>   | Felt                           | ISO 2424                |
| <b>Width</b>               | 400 cm                         | ± 1%<br>EN 984          |
| <b>Pile Weight</b>         | 450 gr/m <sup>2</sup>          | ISO 8543                |
| <b>Total weight</b>        | Felt : 1.260 gr/m <sup>2</sup> | ± 15%<br>ISO 8543       |
| <b>Pile height</b>         | 5.5 mm                         | ± 2 mm<br>ISO 1766      |
| <b>Total Height</b>        | Felt : 7.5 mm                  | ISO 1765                |
| <b>Number of knots</b>     | 62.990 /m <sup>2</sup>         | -7.5% .+10%<br>ISO 1763 |
| <b>Fire Classification</b> | Efl                            | EN 13501-1              |
| <b>Use Area</b>            | Medium domestic use (22)       | EN 1307                 |

## Floorsymbols



## Certificates

|                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>2025<br>Betap Tufting B.V.<br>De Blokmat 29<br>8281 JH Genemuiden<br><br>EN1307<br><br>DOP: 1016#3030<br><br>Reaction to fire:<br>Efl<br><br>Slip resistance: DS<br><br>Felt<br><br>Resilient floor<br>covering to be<br>used within a<br>building | <br>2025<br>Betap Tufting B.V.<br>De Blokmat 29<br>8281 JH Genemuiden<br><br>EN1307<br><br>DOP: 1016#3030-UK<br><br>Reaction to fire:<br>Efl<br><br>Slip resistance: DS<br><br>Felt<br><br>Resilient floor<br>covering to be<br>used within a<br>building |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|