

AVATAR

Manufacturing process	Tufted		ISO 2424
Gauge	5/32" Loop		
Pilecomposition	100% Polypropylene (PP)		ISO 2424
Primary backing	Woven Polypropylene (PP)		ISO 2424
Secondary backing	AB + Felt		ISO 2424
Width	400 cm	± 1%	EN 986
Pile weight	ca. 830 gr/m ²		ISO 8543
Total weight	AB ca. 1972 gr/m ²	Felt ca. 2064 gr/m ²	± 15% ISO 8543
Pile height	ca. 4,9 mm		ISO 1765
Total height	AB ca. 7,0 mm	Felt ca. 8,0 mm	+ 15% / -10% ISO 1765
Number of knots	ca. 85.935 /m ²		+ 10% / -7,5% ISO 1763
Fire classification	AB Efl	Felt Efl	EN 13501-1
Light fastness	5		105-B02
Wearability	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Thermal resistance	0,130 m ² K/W		ISO 8302
Sound isolation	20,0 dB		ISO 10140
GUT Nr.	AB DEEE6285	Felt C40A13B6	

Floorsymbols AB



Floorsymbols Vlies



Certificates

EN 14041 20	EN 14041 20
	
Reaction to fire: Efl	Reaction to fire: Efl
Slip resistance: DS AB DOP: 1058-127731	Slip resistance: DS Felt DOP: 1058-127732
Textile Floorcovering EN1307	Textile Floorcovering EN1307

