

| <b>HD Printed Carpet</b> | <b>ROADTRIP RUG</b>                                |
|--------------------------|----------------------------------------------------|
| Construction             | Level Loop pile                                    |
| Dye Method               | ChromoJet dyeing                                   |
| Yarn Ply                 | 2 ply                                              |
| Guage                    | 1/10"                                              |
| Number of Tufts          | 157600/m2                                          |
| Primary Backing          | P.P.woven cloth                                    |
| Secondary Backing        | Action Back                                        |
| Latex                    | Eco-VAE                                            |
| Size                     | 140x200cm                                          |
| Treatment                | Anti-Stain treatment with foam and heat set method |

|                      |                                 |
|----------------------|---------------------------------|
| Pile height (mm)     | 4 ±0.5mm                        |
| Pile weight (g/m2)   | 450 ±5%                         |
| Total Thickness (mm) | 6 ±5%                           |
| Yarn Component       | 100% nylon 6 (Twist & Heat-set) |

### **Performance**

|                                                                    |                                   |
|--------------------------------------------------------------------|-----------------------------------|
| CRI Green Label Plus                                               | GLP1350                           |
| Fire Classification                                                | BS EN 13501-1:2002                |
| Determination of the burning behaviour using a radiant heat source | BS EN ISO 9239-1:2002             |
| Ignitability when subjected to direct impingement of flame         | BS EN ISO 11925-2:2002            |
| Color Fastness to washing                                          | BS 1006 C06:1990                  |
| Color Fastness to sea water                                        | EN ISO E02:1996                   |
| Color Fastness to light                                            | BS EN ISO 105: B02:1999+amd1:2002 |