

Technical datasheet

PHYSICAL SPECIFICATIONS

Total thickness	EN ISO 24346	2.80 mm
Wear layer	EN ISO 24340	0.55 mm
Wear layer PUR treatment		Ultra-matt coating
Orthophthalate free		Yes
Total weight/m ²	EN ISO 23997	ca. 2500 g/m ²
Width	EN ISO 24341	4 m
Standard length	EN ISO 24341	ca. 30 m

TECHNICAL INFORMATION

Norm	EN ISO 26986	
Usage class	EN ISO 10874	23 - 33
Type of installation		Glueless
Cold welding	Invisiweld	Suitable

PERFORMANCES

Acoustic insulation	EN ISO 717-2	17 dB
Fire classification	EN 13501	Cfl-S1
Slip resistance	EN 13893	DS
Slip restraint	EN 16165 Annex B	R11
Residual indentation	EN ISO 24343-1	norm + 0.20 mm
Thermal conductivity	ISO 8302 (1991)	0.083 (W/m.K)
Heat insulation	EN 12667:2001-01	0.031 (m ² K/W)


ENVIRONMENTAL

Indoor air quality		A+
Recycled content		Total 20% mass balanced
Bio-circular content		10% (Circul'egg)
Green energy derived content		41% (PVC)
Recyclability		100% recyclable
TVOC after 28 days		< 60 µg/m ³
Formaldehyde after 28 days		< 5 µg/m ³

WARRANTY INFORMATION

Warranty	Lifetime
----------	----------

The warranty covers manufacturing defects and premature wear in the event of normal use. The products do not contain any substances from the current candidate list published by ECHA (substances of very high concern) to be published under the REACH regulation. Exclude any rubber parts that may come into direct contact with the flooring (chair ends, furniture, wheels). Use only PVC or polyethylene components. Floorward reserves the right to change or amend any written information without notice. Ensure the latest information is being consulted by referring to the website.



ultra-matt coating



loose lay
up to 45 m²



FLOORWARD



TOTAL 20% MASS BALANCED
RECYCLED CONTENT
POST-CONSUMER | PRE-CONSUMER



eggshells as filler

